

## Certificate of Product Approval

Certificate Number: 913p

Issue: 01

### H S Jackson & Son (Fencing) Limited t/a Jacksons Fencing

Stowting Common  
Ashford  
Kent  
TN25 6BN



is authorised to use the LPCB mark in association with the product(s) listed in this certificate and appendix having complied with the requirements of the standard(s) detailed below:

#### Products

**Defender Xtreme 1**  
security gates

#### Standards

**LPS 1175: Issue 8**  
Requirements and testing procedures for the LPCB certification and listing of intruder resistant building components, strongpoints, security enclosures and free-standing barriers

This certificate and appendix is maintained and held in force through regular surveillance activities

Signed for BRE Global Ltd.

Paul Dillon  
Verifier

17 June 2019  
Date of Issue

17 June 2019  
Date of First Issue



This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit [www.redbooklive.com/terms](http://www.redbooklive.com/terms)).

To check the validity of this certificate and appendix please visit [www.redbooklive.com/check](http://www.redbooklive.com/check), scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX  
T: +44 (0)333 321 8811 E: [enquiries@breglobal.com](mailto:enquiries@breglobal.com)

LPCB is a Registered Trademark of the Building Research Establishment Ltd.



## Appendix to Certificate No: 913p

Issue: 01

H S Jackson & Son (Fencing) Limited t/a Jacksons Fencing

### Security Gates

Product Name	Type	Height (m)	Minimum Width (m)	Maximum Width (m)	Compatible Locking Systems	Security Rating	LPCB Ref. No.
Defender Xtreme 1	Single leaf inward opening security gate	2.25, 2.5 and 3.0	0.855	6.015	1	A1 (SR1)	913p/01
	Single leaf inward opening padlockable security gate		0.848	6.008	2		

### Compatible Locking Devices

Compatible Locking Device	Manufacturer	Model	Type	Compatible Operating Devices		Compatible Cylinders / Padlocks
				External face	Internal face	
1	Locinox	LAKQ U2 lock with SHKL QF keep	Shrouded turn handle key lock	Key and lever handle	Key and lever handle	EVVA A5 DZ27-7KD Euro-profile double cylinder (key:key)
2	H S Jackson & Son (Fencing) Limited	Padlockable slide latch	Sliding bar	Padlock and sliding bar	Padlock and sliding bar	Squire SS50S padlock with Squire 6 pin cylinder

### Notes:

- The gates shall be mounted onto flat topography and are available in configurations to suit either surface mounting onto hard surfaces or embedding within concrete foundations placed in the ground. Furthermore, the local ground onto/into which the gate is installed shall offer compatible strength.
- The gap between the bottom of the gate leaf and the ground must not exceed 60 mm ( $\pm 10$  mm).

This certificate and appendix is maintained and held in force through regular surveillance activities

*P. Dillon*

Signed for BRE Global Ltd.

Paul Dillon  
Verifier

17 June 2019  
Date of Issue

17 June 2019  
Date of First Issue



This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit [www.redbooklive.com/terms](http://www.redbooklive.com/terms)).

To check the validity of this certificate and appendix please visit [www.redbooklive.com/check](http://www.redbooklive.com/check), scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX  
T: +44 (0)333 321 8811 E: [enquiries@breglobal.com](mailto:enquiries@breglobal.com)

LPCB is a Registered Trademark of the Building Research Establishment Ltd.



bre