

Certificate of Product Approval

Certificate Number: 931b

Issue: 01

Aluroll Limited

Unit 12, Artillery Business Park
Park Hall
Oswestry
Shropshire
SY11 4AD



is authorised to use the LPCB mark in association with the product(s) listed in this certificate and appendix having complied with the requirements of the standard(s) detailed below:

Products

P76 Elite
S76 Elite
I100 Elite SR3
I100 Elite SR4
security shutters

Standard

LPS 1175: Issue 7
Requirements and testing procedures for the LPCB approval and listing of intruder resistant building components, strongpoints, security enclosures and free-standing barriers

This certificate and appendix is maintained and held in force through regular surveillance activities

Signed for LPCB

Paul Dillon
Verifier

09 October 2015
Date of Issue

09 October 2015
Date of First Issue



This certificate and appendix remain the property of BRE Global Ltd and is issued subject to terms and conditions (for details visit www.redbooklive.com/terms).

To check the validity of this certificate and appendix please visit www.redbooklive.com/check, scan the QR tag or contact us.

LPCB is part of BRE Global Ltd, Garston, Watford, WD25 9XX
T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: enquiries@breglobal.com



Appendix to Certificate No: 931b

Issue: 01

Aluroll Limited

Security Shutters

Product Name	Type	Minimum Structural Opening Height (m)	Maximum Structural Opening Height (m)	Minimum Structural Opening Width (m)	Maximum Structural Opening Width (m)	Security Rating ¹	LPCB Ref. No.
P76 Elite	Internally face fitted roller shutter	1.5	7.0	1.0	7.0	1	931b/01
	Reveal fitted roller shutter	1.5	7.0	1.0	7.0	1	931b/02
S76 Elite	Internally face fitted roller shutter	1.5	7.0	1.0	7.0	2	931b/03
	Reveal fitted roller shutter	1.5	7.0	1.0	7.0	2	931b/04
I100 Elite SR3	Internally face fitted roller shutter	1.5	5.0	1.0	7.0	3	931b/05
I100 Elite SR4	Internally face fitted roller shutter	1.5	5.0	1.0	7.0	4	931b/06

Approved Configurations and Locking Devices

Product Name	Type	Operation	Locking Devices ²	
			For Structural Opening Widths Up To 2.999 m	For Structural Opening Widths Over 2.999 m
P76 Elite	Internally face fitted roller shutter	Tube ³	Two Hopkins H75 ⁵ pin locks	Two Hopkins H75 ⁵ pin locks and padlockable ground anchor secured with a K-Force rectangular padlock
	Reveal fitted roller shutter	Direct drive ⁴		
S76 Elite	Internally face fitted roller shutter	Tube ³	Two Hopkins H75 ⁵ pin locks	Two Hopkins H75 ⁵ pin locks and padlockable ground anchor secured with a K-Force rectangular padlock
	Reveal fitted roller shutter	Direct drive ⁴		
I100 Elite SR3	Internally face fitted roller shutter	Tube ³	Two Hopkins H75 pin locks	Two Hopkins H75 pin locks and padlockable ground anchor secured with a K-Force rectangular padlock
		Direct drive ⁴		
I100 Elite SR4	Internally face fitted roller shutter	Tube ³	Two Hopkins H75 pin locks	Two Hopkins H75 pin locks and the Aluroll transverse ground locking system
		Direct drive ⁴		

This certificate and appendix is maintained and held in force through regular surveillance activities



Signed for LPCB

Paul Dillon
Verifier

09 October 2015
Date of Issue

09 October 2015
Date of First Issue



This certificate and appendix remain the property of BRE Global Ltd and is issued subject to terms and conditions (for details visit www.redbooklive.com/terms).

To check the validity of this certificate and appendix please visit www.redbooklive.com/check, scan the QR Tag or contact us.

LPCB is part of BRE Global Ltd., Garston, Watford WD25 9XX.

T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: Enquiries@breglobal.com




Appendix to Certificate No: 931b Aluroll Limited

Issue: 01

Approved Installation Configurations

Product Name	Compatible Substrates					
	Aluminium	Brickwork	Brickwork / Concrete Blockwork	Reinforced Brickwork / Blockwork	Reinforced Concrete	Structural Steelwork
P76 Elite	3	3	3	3	3	3
S76 Elite	-	3	3	3	3	3
I100 Elite SR3	-	3	3	3	3	3
I100 Elite SR4	-	-	-	3	3	3

Notes:

1. The security rating is afforded when the roller shutter is closed and all locks are engaged and secured in accordance with the operating and maintenance instructions provided with the product.
2. The locking devices/mechanisms are fitted to the internal face of the product. Certification does not cover the use of locking devices/mechanism other than those listed above. Utilisation of unlisted locking devices/mechanisms may affect the level of security offered by the roller shutter.
3. This type of motor includes the option of an internal chain override.
4. This type of motor includes the option of an internal handle override.
5. The Hopkins H75 pin locks used on the P76 Elite and S76 Elite roller shutters are modified by Aluroll Limited.
6. The approval applies to the shutters when installed strictly in accordance with the following approved manufacturer's instructions:
 - P76 Elite (SR1) – Installation Instructions, Operation & Maintenance Instructions (V2.1).
 - S76 Elite (SR2) – Installation Instructions, Operation & Maintenance Instructions (V2.1).
 - I100 Elite (SR3) – Installation Instructions, Operation & Maintenance Instructions (V2.1).
 - I100 Elite (SR4) – Installation Instructions, Operation & Maintenance Instructions (V2.1).

This certificate and appendix is maintained and held in force through regular surveillance activities



Signed for LPCB

Paul Dillon
Verifier

09 October 2015
Date of Issue

09 October 2015
Date of First Issue



This certificate and appendix remain the property of BRE Global Ltd and is issued subject to terms and conditions (for details visit www.redbooklive.com/terms).

To check the validity of this certificate and appendix please visit www.redbooklive.com/check, scan the QR Tag or contact us.

LPCB is part of BRE Global Ltd., Garston, Watford WD25 9XX.
T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: Enquiries@breglobal.com


